

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Save](#)

[Resource detail](#)
[Citations](#)

ISO 15976:2002 (R2013) Closed end blind rivets with break pull mandrel and protruding head -- St/St

[View on Information Provider website](#)

Abbreviation

ISO 15976:2002

Valid from

01/11/2002

Information provider

International Organisation for Standardization

Author

International Organisation for Standardization

Information type

ISO Standard

Format

PDF

Cited By

[This resource is cited by 1 document \(show Citations\)](#)

Description

ISO 15976 specifies dimensional and mechanical characteristics and application data for closed end blind rivets with break pull mandrel and protruding head, with a steel body (St) and an steel mandrel (St) and with nominal diameters from 3,2 mm up to and including 6,4 mm.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

ISO 15976:2002 (R2013) Closed end blind rivets with break pull mandrel and protruding head -- St/St

This document is CITED BY:

- [AS/NZS 5131:2016](#)

Back

ISO 15976:2002 (R2013) Closed end blind rivets with break pull mandrel and protruding head -- St/St

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

ISO 15976 specifies dimensional and mechanical characteristics and application data for closed end blind rivets with break pull mandrel and protruding head, with a steel body (St) and an steel mandrel (St) and with nominal diameters from 3,2 mm up to and including 6,4 mm.

[View on Information Provider website](#)

[ISO 15976:2002 \(R2013\) Closed end blind rivets with break pull mandrel and protruding head -- St/St](#)

Description

ISO 15976 specifies dimensional and mechanical characteristics and application data for closed end blind rivets with break pull mandrel and protruding head, with a steel body (St) and an steel mandrel (St) and with nominal diameters from 3,2 mm up to and including 6,4 mm.

[View on Information Provider website](#)

This resource does not cite any other resources.

ISO 15976:2002 (R2013) Closed end blind rivets with break pull mandrel and protruding head -- St/St

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print [Save](#) Email

[Feedback](#)

<input type="text"/>		
<input type="text"/>	<input type="text"/>	<input type="text"/>
<input type="text"/>		

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

<input type="text"/>	<input type="text"/>	<input type="text"/>
<input type="text"/>		

[Feedback](#)