kip to main content Skip to primary navigation
Menu
 Home Home About this portal Latest updates
Print <u>Save</u> Email
esource detail
<u>itations</u>
SO 15980:2002 Open end blind rivets with break pull mandrel and countersunk lead St/St iew on Information Provider website {{ linkText }}
bbreviation ISO 15980:2002 alid from
01/11/2002
Iformation provider Standards New Zealand uthor International Organisation for Standardization Iformation type ISO Standard ormat PDF, Hard copy
ited By This resource is cited by 1 document (show Citations)
escription
SO 15980 specifies dimensional and mechanical characteristics and application data for open end blind rivets with break pull andrel and protruding head, with a steel body and a steel mandrel and with nominal diameters from 2,4 mm up to and including .4 mm.
or assistance with locating previous versions, please contact the information provider.
iew on Information Provider website {{ linkText }}

ISO 15980:2002 Open end blind rivets with break pull mandrel and countersunk head -- St/St

This document is CITED BY:

This resource is cited by:

AS/NZS 5131:2016

 $\label{prop:constraints} For assistance with locating previous versions, please contact the information provider.$

Back

ISO 15980:2002 Open end blind rivets with break pull mandrel and countersunk head -- St/St

Show what documents this resource is CITED BY Show what documents this resource CITES

Description

ISO 15980 specifies dimensional and mechanical characteristics and application data for open end blind rivets with break pull mandrel and protruding head, with a steel body and a steel mandrel and with nominal diameters from 2,4 mm up to and including 6,4 mm.

View on Information Provider website

ISO 15980:2002 Open end blind rivets with break pull mandrel and countersunk head -- St/St

Description

Feedback

ISO 15980 specifies dimensional and mechanical characteristics and application data for open end blind rivets with break pull mandrel and protruding head, with a steel body and a steel mandrel and with nominal diameters from 2,4 mm up to and including 6,4 mm.

View on Information Provider website

This resource does not CITE any other resources.

This resource does not cite any other resources.

ISO 15980:2002 Open end blind rivets with break pull mandrel and countersunk head -- St/St

Table of Contents

Print Save Email

Feedback

Contact us
Privacy policy
Disclaimer
Copyright