

Menu

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

Print

[Save](#)

Email

[Resource detail](#)

[Citations](#)

ISO 2566-2:1984: Steel - Conversion of elongation values Part 2: Austenitic Steel

[View on Information Provider website](#)

Abbreviation

ISO 2566-2:1984

Valid from

01/08/1984

Information provider

Standards Australia

Information type

Australian Standard

Format

Hard copy, PDF

Cited By

[This resource is cited by 2 documents \(show Citations\)](#)

Description

Specifies a method of converting room temperature percentage elongations after fracture obtained on various proportional and non-proportional gauge lengths to other gauge lengths.

The conversions are not applicable to cold reduced steels, quenched and tempered steels and non-austenitic steels, or where certain tensile strength ranges and dimensions are exceeded.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#) {{ linkText }}

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

ISO 2566-2:1984: Steel - Conversion of elongation values Part 2: Austenitic Steel

This document is CITED BY:

- [AS 1391-2007](#)

ISO 2566-2:1984 is cited by AS 1391-2007 Metallic materials - Tensile testing at ambient temperature

- [BS EN 10253-3:2008](#)

ISO 2566-2:1984 is cited by BS EN 10253-3:2008 Butt-welding pipe fittings - wrought austenitic and austenitic-ferritic (duplex) stainless steels without specific inspection requirements

Back

ISO 2566-2:1984: Steel - Conversion of elongation values Part 2: Austenitic Steel

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

Specifies a method of converting room temperature percentage elongations after fracture obtained on various proportional and non-proportional gauge lengths to other gauge lengths.

The conversions are not applicable to cold reduced steels, quenched and tempered steels and non-austenitic steels, or where certain tensile strength ranges and dimensions are exceeded.

[View on Information Provider website](#)

[ISO 2566-2:1984: Steel - Conversion of elongation values Part 2: Austenitic Steel](#)

Description

Specifies a method of converting room temperature percentage elongations after fracture obtained

on various proportional and non-proportional gauge lengths to other gauge lengths.

The conversions are not applicable to cold reduced steels, quenched and tempered steels and non-austenitic steels, or where certain tensile strength ranges and dimensions are exceeded.

[View on Information Provider website](#)

This resource does not cite any other resources.

ISO 2566-2:1984: Steel - Conversion of elongation values Part 2: Austenitic Steel

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print [Save](#) Email

[Feedback](#)

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

[Feedback](#)