

Menu

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

Print

[Save](#)

Email

[Resource detail](#)

[Citations](#)

ISO 3459:1976 Polyethylene (PE) pressure pipes - Joints assembled with mechanical fittings - Internal under-pressure test method and requirement

[View on Information Provider website](#)

Abbreviation

ISO 3459:1976

Valid from

01/10/1976

Information provider

Standards New Zealand

Author

International Organization for Standardization

Information type

ISO Standard

Format

PDF

Cited By

[This resource is cited by 2 documents \(show Citations\)](#)

Description

Specification of the test method and apparatuses for checking the leakproofness of assembled joints, when the external pressure is greater than the pressure within the pipe. The test shall be carried out at two levels of difference between external and internal pressures (0,01 and 0,08 MPa).

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#) {{ linkText }}

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

ISO 3459:1976 Polyethylene (PE) pressure pipes - Joints assembled with mechanical fittings - Internal under-pressure test method and requirement

This document is CITED BY:

- [AS/NZS 2845.1:2010](#)

ISO 3459:1976 is cited by AS/NZS 2845.1:2010 Water supply - Backflow prevention devices - Part 1: Materials, design and performance requirements

- [AS/NZS 4129:2008](#)

ISO 3459:1976 is cited by AS/NZS 4129:2008 Fittings for polyethylene (PE) pipes for pressure applications

[Back](#)

ISO 3459:1976 Polyethylene (PE) pressure pipes - Joints assembled with mechanical fittings - Internal under-pressure test method and requirement

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

Specification of the test method and apparatuses for checking the leakproofness of assembled joints, when the external pressure is greater than the pressure within the pipe. The test shall be carried out at two levels of difference between external and internal pressures (0,01 and 0,08 MPa).

[View on Information Provider website](#)

[ISO 3459:1976 Polyethylene \(PE\) pressure pipes - Joints assembled with mechanical fittings - Internal under-pressure test method and requirement](#)

Description

Specification of the test method and apparatuses for checking the leakproofness of assembled joints, when the external pressure is greater than the pressure within the pipe. The test shall be carried out at two levels of difference between external and internal pressures (0,01 and 0,08 MPa).

[View on Information Provider website](#)

This resource does not cite any other resources.

ISO 3459:1976 Polyethylene (PE) pressure pipes - Joints assembled with mechanical fittings - Internal under-pressure test method and requirement

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print [Save](#) Email

[Feedback](#)

<input type="text"/>	<input type="text"/>	<input type="text"/>
----------------------	----------------------	----------------------

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

<input type="text"/>	<input type="text"/>	<input type="text"/>
----------------------	----------------------	----------------------

[Feedback](#)