

Menu

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

Print

[Save](#)

Email

[Resource detail](#)

[Citations](#)

## ISO 3508:1976 Thread run-outs for fasteners with thread in accordance with ISO 261 and ISO 262

[View on Information Provider website](#)

Abbreviation

ISO 3508:1976

Valid from

01/02/1976

---

Information provider

Standards New Zealand

Author

International Organisation for Standardization

Information type

ISO Standard

Format

PDF

---

Cited By

[This resource is cited by 1 document \(show Citations\)](#)

---

**Description**

This Standard specifies for fully threaded screws with machined, or rolled threads pitches of the thread ranging from 0,2 mm to 6 mm and thread diameters (coarse thread) ranging from 1 mm to 68 mm; it does not apply to those threaded fasteners where special requirements are laid down in the product standards.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#) {{ linkText }}

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

## ISO 3508:1976 Thread run-outs for fasteners with thread in accordance with ISO 261 and ISO 262

This document is CITED BY:

- [BS EN 14399-3:2015](#)

ISO 3508:1976 is cited by BS EN 14399-3:2015 High-strength structural bolting assemblies for preloading. System HR. Hexagon bolt and nut assemblies

[Back](#)

## ISO 3508:1976 Thread run-outs for fasteners with thread in accordance with ISO 261 and ISO 262

Show what documents this resource is CITED BY

Show what documents this resource CITES

### Description

This Standard specifies for fully threaded screws with machined, or rolled threads pitches of the thread ranging from 0,2 mm to 6 mm and thread diameters (coarse thread) ranging from 1 mm to 68 mm; it does not apply to those threaded fasteners where special requirements are laid down in the product standards.

[View on Information Provider website](#)

[ISO 3508:1976 Thread run-outs for fasteners with thread in accordance with ISO 261 and ISO 262](#)

### Description

This Standard specifies for fully threaded screws with machined, or rolled threads pitches of the thread ranging from 0,2 mm to 6 mm and thread diameters (coarse thread) ranging from 1 mm to 68 mm; it does not apply to those threaded fasteners where special requirements are laid down in the product standards.

[View on Information Provider website](#)

This resource does not cite any other resources.

# ISO 3508:1976 Thread run-outs for fasteners with thread in accordance with ISO 261 and ISO 262

This resource does not CITE any other resources.

Back

Close

## Table of Contents

Print

[Save](#)

Email

[Feedback](#)

<input type="text"/>	<input type="text"/>	<input type="text"/>
----------------------	----------------------	----------------------

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

<input type="text"/>	<input type="text"/>	<input type="text"/>
----------------------	----------------------	----------------------

[Feedback](#)