

Menu

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Save](#)

[Resource detail](#)

[Citations](#)

ISO 8773:1991 Polypropylene (PP) pipes and fittings for buried drainage and sewerage systems - Specifications

[View on Information Provider website](#)

Abbreviation

ISO 8773:1991

Valid from

16/05/1991

Information provider

Standards New Zealand

Author

International Organization for Standardization

Information type

ISO Standard

Format

PDF

Cited By

[This resource is cited by 1 document \(show Citations\)](#)

Description

This International Standard specifies requirements for polypropylene (PP) homopolymer and copolymer pipes, fittings and joints with nominal outside diameters from 110 mm to 2,000 mm and for fittings with elastomeric sealing rings of nominal outside diameter from 110 mm to 400 mm, serving as buried gravity drain and sewer pipes for the transportation of soil and waste discharge of domestic origin.

It may also be applied to pipes, fittings and joints for discharges of industrial origin, provided chemical and temperature resistance is taken into account.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

ISO 8773:1991 Polypropylene (PP) pipes and fittings for buried drainage and sewerage systems - Specifications

This document is CITED BY:

- [AS/NZS 5065:2005](#)

ISO 8773:1991 is cited by AS/NZS 5065:2005 Polyethylene and polypropylene pipes and fittings for drainage and sewerage applications

ISO 8773:1991 Polypropylene (PP) pipes and fittings for buried drainage and sewerage systems - Specifications

Description

This International Standard specifies requirements for polypropylene (PP) homopolymer and copolymer pipes, fittings and joints with nominal outside diameters from 110 mm to 2,000 mm and for fittings with elastomeric sealing rings of nominal outside diameter from 110 mm to 400 mm, serving as buried gravity drain and sewer pipes for the transportation of soil and waste discharge of domestic origin.

It may also be applied to pipes, fittings and joints for discharges of industrial origin, provided chemical and temperature resistance is taken into account.

[View on Information Provider website](#)

[ISO 8773:1991 Polypropylene \(PP\) pipes and fittings for buried drainage and sewerage systems - Specifications](#)

Description

This International Standard specifies requirements for polypropylene (PP) homopolymer and copolymer pipes, fittings and joints with nominal outside diameters from 110 mm to 2,000 mm and for fittings with elastomeric sealing rings of nominal outside diameter from 110 mm to 400 mm, serving as buried gravity drain and sewer pipes for the transportation of soil and waste discharge of domestic origin.

It may also be applied to pipes, fittings and joints for discharges of industrial origin, provided chemical and temperature resistance is taken into account.

[View on Information Provider website](#)

This resource does not cite any other resources.

ISO 8773:1991 Polypropylene (PP) pipes and fittings for buried drainage and sewerage systems - Specifications

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print

[Save](#)

Email

[Feedback](#)

<input type="text"/>	<input type="text"/>	<input type="text"/>
----------------------	----------------------	----------------------

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

<input type="text"/>	<input type="text"/>	<input type="text"/>
----------------------	----------------------	----------------------

[Feedback](#)