

Menu

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

Print

[Save](#)

Email

[Resource detail](#)

[Citations](#)

Nailing the fit - Build 166 (2018)

[View on Information Provider website](#) [Download this resource \(PDF, 1.6MB\)](#)

{{ linkText }}

Abbreviation

Nailing the fit - Build 166 (2018)

Valid from

01/06/2018

Information provider

BRANZ Limited

Information type

BUILD article

Format

Website, PDF

Description

Builders shouldn't make do with a poor fit as this can bring a range of problems. If the fit is less than perfect, what amount of variation can be tolerated before rework is required?

Construction of all building types requires a good fit – whether it's a window into an opening, glazing into the frame or a cladding panel installed between or in front of columns. All construction work must incorporate an allowance for inherent variances in construction materials and workmanship skills.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#) [Download this resource \(PDF, 1.6MB\)](#)

{{ linkText }}

For assistance with locating previous versions, please contact the information provider.

This resource is not cited by any other resources.

Nailing the fit - Build 166 (2018)

This document is not CITED BY any other resources:

Back

Nailing the fit - Build 166 (2018)

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

Builders shouldn't make do with a poor fit as this can bring a range of problems. If the fit is less than perfect, what amount of variation can be tolerated before rework is required?

Construction of all building types requires a good fit – whether it's a window into an opening, glazing into the frame or a cladding panel installed between or in front of columns. All construction work must incorporate an allowance for inherent variances in construction materials and workmanship skills.

[View on Information Provider website](#) [Download this resource \(PDF, 1.6MB\)](#)

[Nailing the fit - Build 166 \(2018\)](#)

Description

Builders shouldn't make do with a poor fit as this can bring a range of problems. If the fit is less than perfect, what amount of variation can be tolerated before rework is required?

Construction of all building types requires a good fit – whether it's a window into an opening, glazing into the frame or a cladding panel installed between or in front of columns. All construction work must incorporate an allowance for inherent variances in construction materials and workmanship skills.

[View on Information Provider website](#) [Download this resource \(PDF, 1.6MB\)](#)

This resource does not cite any other resources.

Nailing the fit - Build 166 (2018)

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print

[Save](#)

Email

[Feedback](#)

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

[Feedback](#)