

Menu

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

Print

[Save](#)

Email

[Resource detail](#)

[Citations](#)

## NZS 6401:1973 Specification for PVC-insulated cables for electric power and lighting

[View on Information Provider website](#)

Abbreviation

NZS 6401:1973

Valid from

30/11/1973

---

Information provider

Standards New Zealand

Author

Standards New Zealand

Information type

New Zealand Standard

Format

PDF

---

Cited By

[This resource is cited by 1 document \(show Citations\)](#)

---

Description

This Standard relates to 600/1000 V rated cables made in New Zealand and commonly used for fixed wiring installations.

It includes insulated conduit wire, sheathed single-core and multi-core cables, and neutral-screened cables, suitable for use where the combination of ambient temperature and temperature rise due to load results in a conductor temperature not exceeding 70°C. Conductor sizes range from 1.0 mm<sup>2</sup> to

630 mm<sup>2</sup>.

Conductor materials provided for are copper and aluminium.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

## **NZS 6401:1973 Specification for PVC-insulated cables for electric power and lighting**

This document is CITED BY:

- [G12/AS1 \(Third Edition, Amendment 7\)](#)

NZS 6401:1973 is cited by Acceptable Solution G12/AS1: Water Supplies from 01/12/2007

## **NZS 6401:1973 Specification for PVC-insulated cables for electric power and lighting**

### **Description**

This Standard relates to 600/1000 V rated cables made in New Zealand and commonly used for fixed wiring installations.

It includes insulated conduit wire, sheathed single-core and multi-core cables, and neutral-screened cables, suitable for use where the combination of ambient temperature and temperature rise due to load results in a conductor temperature not exceeding 70°C. Conductor sizes range from 1.0 mm<sup>2</sup> to 630 mm<sup>2</sup>.

Conductor materials provided for are copper and aluminium.

[View on Information Provider website](#)

[NZS 6401:1973 Specification for PVC-insulated cables for electric power and lighting](#)

## Description

This Standard relates to 600/1000 V rated cables made in New Zealand and commonly used for fixed wiring installations.

It includes insulated conduit wire, sheathed single-core and multi-core cables, and neutral-screened cables, suitable for use where the combination of ambient temperature and temperature rise due to load results in a conductor temperature not exceeding 70°C. Conductor sizes range from 1.0 mm<sup>2</sup> to 630 mm<sup>2</sup>.

Conductor materials provided for are copper and aluminium.

[View on Information Provider website](#)

This resource does not cite any other resources.

# NZS 6401:1973 Specification for PVC-insulated cables for electric power and lighting

This resource does not CITE any other resources.

Back

Close

## Table of Contents

Print [Save](#) Email

[Feedback](#)


- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)


[Feedback](#)