

Menu

- [Home](#)
- [About this portal](#)
- [Latest updates](#)

Print

[Save](#)

Email

[Resource detail](#)

[Citations](#)

Replacing a concrete or masonry tile roof - Build 168 (2018)

[Download this resource \(PDF, 742KB\)](#)

Abbreviation

Replacing a concrete or masonry tile roof

Valid from

01/10/2018

Information provider

BRANZ Limited

Information type

BUILD article

Format

PDF

Description

THE REPLACEMENT of a heavy concrete or masonry tile roof with a lightweight roofing material, such as profiled metal, should be relatively straightforward as the structure should easily be able to support the lighter load.

Considering wind uplift should be top of mind when replacing a heavy roof with a lighter one, NZS 3604:2011 Timber-framed buildings outlines the necessary top plate connections.

For assistance with locating previous versions, please contact the information provider.

[Download this resource \(PDF, 742KB\)](#)

For assistance with locating previous versions, please contact the information provider.

This resource is not cited by any other resources.

Replacing a concrete or masonry tile roof - Build 168 (2018)

This document is not CITED BY any other resources:

Back

Replacing a concrete or masonry tile roof - Build 168 (2018)

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

THE REPLACEMENT of a heavy concrete or masonry tile roof with a lightweight roofing material, such as profiled metal, should be relatively straightforward as the structure should easily be able to support the lighter load.

Considering wind uplift should be top of mind when replacing a heavy roof with a lighter one, NZS 3604:2011 Timber-framed buildings outlines the necessary top plate connections.

[Download this resource \(PDF, 742KB\)](#)

[Replacing a concrete or masonry tile roof - Build 168 \(2018\)](#)

Description

THE REPLACEMENT of a heavy concrete or masonry tile roof with a lightweight roofing material, such as profiled metal, should be relatively straightforward as the structure should easily be able to support the lighter load.

Considering wind uplift should be top of mind when replacing a heavy roof with a lighter one, NZS 3604:2011 Timber-framed buildings outlines the necessary top plate connections.

[Download this resource \(PDF, 742KB\)](#)

This resource does not cite any other resources.

Replacing a concrete or masonry tile roof - Build 168 (2018)

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print [Save](#) Email

[Feedback](#)

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

[Feedback](#)